Product fiche compliant to Commission Delegate REGULATION (UK)/(EU) No 65/2014

Supplier	**WS Westin Ltd**		
Model Identifier	**STRATUS EDGE 1200 x 440**		
Product Data	***Symbol***	***Unit***	***Value***
Annual Energy Consumption	AEC_{hood}	KWh/a	78.5
Energy Efficiency Class			B
Fluid Dynamic Efficiency	FDE_{hood}		30.9
Fluid Dynamic Efficiency Class			A
Light Efficiency	LE_{hood}	lux/W	9.4
Light Efficiency Class			E
Grease Filtering Efficiency	GFE_{hood}	%	52.8
Grease Filtering Efficiency Class			F
Minimum Airflow in Normal Use		m^3/hr	206.8
Maximum Airflow in Normal Use		m^3/hr	511.4
Airflow at Intensive Setting		m^3/hr	772.2
A-weighted Sound Power at Minimum Speed		dB(A)	46
A-weighted Sound Power at Maximum Speed		dB(A)	63
A-weighted Sound Power at Intensive Speed		dB(A)	71
Power Consumption in Off Mode	Po	W	0.00
Power Consumption in Standby Mode	Ps	W	0.37

Additional data compliant to Commission Delegate REGULATION (UK)/(EU) No 66/2014

Time Increase Factor	f		0.9
Energy Efficiency Index	EEI_{hood}	%	63.1
Measured Air Flow at Best Efficiency Point	Q_{BEP}	m^3/hr	414.3
Measured Air Pressure at Best Efficiency Point	P_{BEP}	Pa	443
Maximum Air Flow	Q_{Max}	m^3/hr	790.3
Measured Electric Power Input at Best Efficiency Point	W_{BEP}	W	164.8
Nominal Power of Lighting System	W_L	W	33.4
Average Illumination of Lighting System on cooktop	E_{MIDDLE}	lux	314

Products manufactured in accordance with harmonised standards:
Safety: IEC/EN 60335-1; IEC/EN 60335-2-31, IEC/EN 62233. **Performance:** IEC/EN 61591; ISO 5167-1; ISO 5167-3; ISO 5168; IEC/EN 60704-1; IEC/EN 60704-2-13; ISO 3741; EN 50564; IEC 62301. **EMC:** EN 55014-1; CISPR 14-1; EN 55014-2; CISPR 14-2; IEC/EN 61000-3-2; IEC/EN 61000-3-3.

Suggestions for reducing the environmental impact of this product:
When you start cooking run the extractor at the lowest speed setting, only increasing the motor speed when fumes and cooking vapours require you to do so.
The appliance works more efficiently the shorter and straighter your duct run. Design your installation so that the duct length and number of bends are minimised.
Follow all recommendations relating to installation, use and maintenance described in the product manual.