

**Island mounted
Pureline Frame 90 cm
Black**



EAN 5414425230624

Functions & features

▪ Motor	Integrated
▪ Sound absorber	Integrated
▪ Recirculation	Standard, Monoblock
▪ InTouch function	Standard
▪ Auto stop	▪
▪ Delayed switch off (minutes)	30
▪ Grease filter	6830020
▪ Number of grease filters	2
▪ Grease filter cleaning indication	▪
▪ Recirculation filter cleaning indication	▪
▪ Control method	Push buttons + Remote control
▪ Number of speeds	3 + power
▪ Automatic Power revert (minutes)	6

Dimensions

▪ Product dimensions recirculation (WxDxHmin-Hmax) (mm)	872 x 556 x 700 -
▪ Advised mounting height induction hobs (Hmin-Hmax) (mm)	650 - 850
▪ Advised mounting height gas hobs (Hmin-Hmax) (mm)	650 - 850
▪ Advised mounting height ceramic hobs (Hmin-Hmax) (mm)	650 - 850
▪ Position exhaust	Top

Frame Dimensions

▪ Frame Dimensions (WxDxH) (mm)	25 x 806 x 700
▪ Number of frames	2
▪ Cut-out lower shelf (WxD) (mm)	845 x 485
▪ Dimensions housing cooker hood (WxDxH) (mm)	872 x 556 x 330
▪ Width cut-out top shelf (mm)	401
▪ Thickness of shelf material (mm)	18 - 25
▪ Depth of shelf material (mm)	750
▪ Frame width (mm)	25
▪ Frame depth (mm)	806
▪ Frame height (mm)	700
▪ Width cut-out lower shelf (mm)	845
▪ Depth cut-out lower shelf (mm)	485
▪ Width housing cooker hood (mm)	872
▪ Depth housing cooker hood (mm)	556
▪ Height housing cooker hood (mm)	330
▪ Depth cut-out top shelf (mm)	248
▪ Cut-out top shelf (WxD) (mm)	401 x 248

Lighting

▪ Functional lighting type	LED
▪ Functional light dimmable	▪

Lighting

▪ Soft-ON/OFF	-
▪ Number of functional lights	4
▪ Total energy consumption functional light (W)	8
▪ Color functional light (K)	2700/4000

Airflow and noise level

▪ Free airflow (m ³ /h)	815
▪ Airflow (m ³ /h) measured according to EN 61591	
▪ Sound regulation according to	
▪ Airflow duct out speed 1 (m ³ /h)	251
▪ Airflow duct out speed 2 (m ³ /h)	363
▪ Airflow duct out speed 3 (m ³ /h)	423
▪ Airflow duct out max powerspeed (m ³ /h) (Qboost)	497
▪ Sound pressure duct out speed 1 (dB(A)) / Sound power duct out speed 1 (dB(A))	35 / 47
▪ Sound pressure duct out speed 2 (dB(A)) / Sound power duct out speed 2 (dB(A))	43 / 55
▪ Sound pressure duct out speed 3 (dB(A)) / Sound power duct out speed 3 (dB(A))	46 / 58
▪ Sound pressure duct out at max powerspeed (dB(A)) / Sound power duct out at max powerspeed (dB(A)) (LWAboost)	49 / 61

Technical specifications

▪ Maximum power (W)	117
▪ Voltage appliance (V)	230
▪ Frequency (Hz)	50
▪ Net weight (kg)	50
▪ Length power supply cable (m)	1,8

15001 / 15003 / 15005 / 15007 / 15009 / 15011

